



# EverBase® Specifications

Questions?

Call us today at 855.647.6909

or contact us by email at

sales@versare.com



Recyclable, chemical-resistant and waterproof, EverBase modular flooring interconnects to create a seamless floor surface and solid support base. Suitable for structures like exhibit floors, game courts, event surfaces and garage floors.

## Material

High-impact Polypropylene co-polymer (“no-break”) with UV inhibitors added for outdoor use.

## Warranty

Standard 2-year warranty against manufacturer’s defects.

## Size


12” x 12”

## Thickness

1.1”

## Weight

1.27 lbs/tile



Solid Top



Drainage Top  
Use alone or with EverBlock  
Connector Lug

## Colors\*

EverBase® comes in 16 colors in both solid top and drainage top



\*Custom colors available with minimum order sizes.

\*\*Color contains metallic sheen additive

## Shipping Quantities

Standard Pallet:	40” x 48” x 84”	630 sf
53ft Truckload Qty:	26 Pallets	16,380 sf
20ft Ocean Container:	10 Pallets	6,300 sf
40ft Ocean Container:	20 Pallets	12,600 sf
40ft h Cube Ocean Container:	20 Extra Tall Pallets	12,600 sf
Military 463L Pallet (88” x 98” x 96”):	2,400 sf Max Loading	

## Weight Loading Capacity

8,600 lbs/sf\*

*\*On a solid subsurface, non-moving (static) weight, with equal distribution of load across the tile surface.*

Support structure: Intersecting bi-directional support ribs provide structure, torsional strength, and additional weight distribution and weight loading capabilities.

## Accessories

Male and female edge connector ramps make the EverBase® system ADA compliant for pedestrian access points and assist in areas where wheeled equipment is expected to come onto the floor. Connector lugs allow you to securely build and add on with the EverBlock modular block system.



Male Ramp  
6" x 12", Black



Female Ramp  
6" x 12", Black



Corner Ramp  
6" x 6", Black



Connector Lug  
2" x 2", Black



Use EverBlock modular blocks underneath to create a stage or platform

## Fire Rating

UL94HB (Underwriters Laboratory Test):

This test signifies EverBase does not flare up when exposed to an open flame and has a slow burn rate of 2" wide, 0.5 mil thickness test sample. EverBase meets all applicable standards for temporary floor covers.

Hot wire ignition rating: 3

ATSM 2859 (Flammability of Finished Textile Floor Covering Materials): Pass

## Features

- Toolless assembly
- May be installed on top of EverBlock® modular building blocks to raise floor
- UV Protected
- 100% Recyclable
- Drainage Top option allows water and light through to protect grass

